

Mold Release Lubricant

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)
Issue date: 9/12/2025 Version: 1.0

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture
Trade name : Mold Release Lubricant

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Lubricant
Restrictions on use : Only use as directed on package labeling

1.4. Supplier's details

ASTEMREY LLC
312 W 2 ND ST
UNIT A2013
CASPER, WY 82601
USA
T +1 (904) 852-6653
support@astemrey.com

1.5. Emergency phone number

Emergency number : For Hazardous Materials or Dangerous Goods Incident Spill, Leak, Fire, Exposure, or Accident
Call CHEMTREC Day or Night: 1-800-424-9300 (Toll Free, USA) / 703-527-3887 (Virginia, USA)
CCN 1022189
Back-up Emergency Number: +1 703-741-5970 (Washington, DC)

SECTION 2 Hazard Identification

2.1. Classification of the substance or mixture

GHS US classification

Aerosol, Category 1	H222;H229	Extremely flammable aerosol. Pressurized container; may burst if heated.
Skin corrosion/irritation, Category 2	H315	Causes skin irritation.
Reproductive toxicity, Category 2	H361	Suspected of damaging fertility.
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336	May cause drowsiness or dizziness.
Specific target organ toxicity — Repeated exposure, Category 1	H372	Causes damage to organs (nervous system) through prolonged or repeated exposure (Inhalation).
Aspiration hazard, Category 1	H304	May be fatal if swallowed and enters airways.
Full text of H statements : see section 16		

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger

Mold Release Lubricant

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Hazard statements (GHS US)	: H222 - Extremely flammable aerosol H229 - Pressurized container; may burst if heated H304 - May be fatal if swallowed and enters airways H315 - Causes skin irritation H336 - May cause drowsiness or dizziness H361 - Suspected of damaging fertility. H372 - Causes damage to organs (nervous system) through prolonged or repeated exposure (Inhalation)
Precautionary statements (GHS US)	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe mist, spray, vapors. Wash hands, forearms and face thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves, eye protection. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. If on skin: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice or attention. Take off contaminated clothing and wash it before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. If exposed or concerned: Get medical advice/attention. Call a poison center or doctor if you feel unwell. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C). Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

No additional information available

2.5. Unknown acute toxicity

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

Mold Release Lubricant

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Hexane	CAS-No.: 110-54-3	32	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Isobutane	CAS-No.: 75-28-5	25	Flam. Gas 1A, H220 Press. Gas (Comp.), H280
Butane	CAS-No.: 106-97-8	23	Flam. Gas 1A, H220 Press. Gas (Comp.), H280 Simple Asphy. 1, SIAS
Propane	CAS-No.: 74-98-6	12	Flam. Gas 1, H220 Press. Gas (Comp.), H280 Simple Asphy., SIAS
Silicone oil	CAS-No.: 63148-62-9	8	Not classified

Full text of hazard classes and H-statements : see section 16

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	: First aider: Pay attention to self-protection. Never give anything by mouth to an unconscious person. Give artificial respiration if necessary. Induce artificial respiration with mask fitted with one-way valve or other suitable device but, not mouth-to-mouth. Call a physician immediately.
First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If the victim is unconscious: Lay in a stable manner on victim's side. Induce artificial respiration with mask fitted with one-way valve or other suitable device; not mouth-to-mouth. Call a physician immediately.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin areas with mild soap and water, followed by warm water rinse. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Call a physician immediately.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: Aspiration of the product into the lungs may cause very serious pneumonia. May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Irritation (itching, redness, blistering).
Symptoms/effects after eye contact	: May cause eye irritation.
Symptoms/effects after ingestion	: Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis.
Most Important Symptoms/Effects	: Risk of product entering the lungs on vomiting after ingestion.
Chronic symptoms	: Causes damage to organs (nervous system) through prolonged or repeated exposure (inhalation). Suspected of damaging fertility.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: IF exposed or concerned: Get medical advice/attention.
-----------------------------------	--

Mold Release Lubricant

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Dry chemical, CO₂, or water spray or regular foam.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard : Extremely flammable aerosol.

Explosion hazard : Vapors in confined areas may explode when exposed to fire. Extremely flammable chemical under pressure: May explode if heated.

Hazardous decomposition products in case of fire : Toxic fumes may be released. Carbon dioxide. Carbon monoxide.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection. Move containers from fire area if it can be done without personal risk. Use water spray or fog for cooling exposed containers. Large fires: Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Withdraw immediately in case of rising sound from venting devices or discoloration from tank. ALWAYS stay away from tanks engulfed in fire. For a massive fire, use unmanned hose holders or monitor nozzles, or withdraw from the area and allow fire to burn. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Avoid all personal contact including breathing in the mist, spray, vapors. Do not take actions involving personal risks. Absorb spillage to prevent material-damage. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters.

For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.

Emergency procedures : Evacuate the danger area. If outdoors, move to an area upwind of the danger area. Do not breathe mist, spray, vapors. Avoid contact with skin and eyes. If possible without taking personal risks, Remove ignition sources, ventilate area. Prevent other non-emergency personnel from entering the danger area. No open flames, no sparks, and no smoking.

For emergency responders

Protective equipment : Wear the recommended personal protective equipment. Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Evacuate personnel to a safe area. Stop leak if safe to do so. Remove all sources of ignition. Use non-sparking tools.

Environmental precautions : Do not let the product reach soil, drains, sewers, or surface and ground water.

6.2. Methods and materials for containment and cleaning up

For containment : Contain with non-combustible inert absorbent. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk. All equipment used when handling the product must be grounded.

Mold Release Lubricant

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Methods for cleaning up : Take up in non-combustible inert absorbent and place into container for disposal. Contaminated absorbent material may pose the same hazard as the spilt product. Decontaminate surfaces and equipment with water and detergent. Until a sufficient level of dilution is achieved, the decontamination water may pose the same hazards as the product. Notify authorities if product enters sewers or public waters. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

For further information refer to section 8: "Exposure controls/personal protection", For further information refer to section 13

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Wear personal protective equipment. Do not breathe mist, spray, vapors. Avoid contact with skin, eyes and clothing. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Take precautionary measures against static discharge.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wash contaminated clothing before reuse.

Additional hazards when processed : Proper grounding procedures to avoid static electricity should be followed.

7.2. Conditions for safe storage, including incompatibilities

Storage conditions : Store in a cool, dry and well-ventilated area away from incompatible substances. Store containers in location free from fire risk and away from sources of heat and ignition. Protect from sunlight. Always keep container in upright position.

Incompatible materials : Strong oxidizing agents. Strong acids. Strong bases.

Heat-ignition : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Packaging materials : Store always product in container of same material as original container.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Hexane (110-54-3)

USA - ACGIH - Occupational Exposure Limits

Local name	n-Hexane
ACGIH® TLV® TWA	176 mg/m ³ 50 ppm Skin - potential significant contribution to overall exposure by the cutaneous route
Remark (ACGIH)	TLV® Basis: CNS impair; Peripheral neuropathy; Eye & URT irr. Notations: Skin; BEI
Regulatory reference	ACGIH 2025

USA - ACGIH - Biological Exposure Indices

Local name	n-Hexane
BEI	0.5 mg/l Parameter: 2,5-Hexanedione - Medium: urine - Sampling time: End of shift
Regulatory reference	ACGIH 2025

USA - OSHA - Occupational Exposure Limits

Local name	n-Hexane
------------	----------

Mold Release Lubricant

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Hexane (110-54-3)	
OSHA PEL TWA	1800 mg/m ³
	500 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - NIOSH - Occupational Exposure Limits	
Local name	n-Hexane
NIOSH REL 10h TWA	50 ppm
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-1 (NIOSH Pocket Guide to Chemical Hazards (NPG))
Propane (74-98-6)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Propane
Remark (ACGIH)	TLV® Basis: Asphyxia
Regulatory reference	ACGIH 2025
USA - OSHA - Occupational Exposure Limits	
Local name	Propane
OSHA PEL TWA	1800 mg/m ³
	1000 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - NIOSH - Occupational Exposure Limits	
Local name	Propane
NIOSH REL 10h TWA	1000 ppm
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-1 (NIOSH Pocket Guide to Chemical Hazards (NPG))
Butane (106-97-8)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Butane
ACGIH® TLV® STEL	2370 mg/m ³ (EX - Explosion hazard)
	1000 ppm (EX - Explosion hazard)
Remark (ACGIH)	TLV® Basis: CNS impair
Regulatory reference	ACGIH 2025
Isobutane (75-28-5)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Isobutane
ACGIH® TLV® STEL	2370 mg/m ³ (EX - Explosion hazard)
	1000 ppm (EX - Explosion hazard)
Remark (ACGIH)	TLV® Basis: CNS impair
Regulatory reference	ACGIH 2025

Mold Release Lubricant

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station. Use general ventilation, local exhaust ventilation, or process enclosure to keep the airborne concentrations below the permissible exposure limits. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
Environmental exposure controls	: Avoid release to the environment. Take measures to reduce or limit air emissions and releases to soil and the aquatic environment.

8.3. Individual protection measures, such as personal protective equipment

Personal protective equipment:

Personal protective equipment should be chosen according to national standards and in discussion with the supplier of the protective equipment. Wear recommended personal protective equipment.

Hand protection:

Wear protective gloves. Chemically impervious gloves as described by OSHA's hand protection regulations in 29 CFR 1910.138

Eye protection:

Wear safety glasses which protect from splashes

Skin and body protection:

Body protection should be chosen depending on activity and possible exposure. Wear fire/flammable resistant/retardant clothing. Antistatic clothing

Respiratory protection:

Use NIOSH approved respirator if ventilation is inadequate. SCBA for emergency responders. Must be used in accordance with an OSHA compliant respiratory protection program.

Personal protective equipment symbol(s):



SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosol can.
Color	: No data available
Odor	: Characteristic
Odor threshold	: No data available
pH	: 6.31 – 6.41
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: -44 °C / -47.2 °F
Flammability (solid, gas)	: Extremely flammable aerosol.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Density	: 0.78 – 0.82 g/cm ³ @ 25 °C / 77 °F
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: 331 °C / 627.8 °F

Mold Release Lubricant

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Explosion limits	: Lower explosion limit: 1.39 vol % Upper explosion limit: 8.38 vol %
Explosive properties	: Pressurized container: may burst if heated.
Particle characteristics	: No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurized container: may burst if heated.

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition. Incompatible materials. Protect from sunlight. Prevent shock/impact.

10.5. Incompatible materials

Strong oxidizing agents. Strong acids. Strong bases.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition generates: Carbon dioxide. Carbon monoxide.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Hexane

LD50 oral rat	24 ml/kg
LD50 dermal rabbit	> 3350 mg/kg
LC50 Inhalation - Rat (Vapors)	259.354 mg/l

Butane

LC50 Inhalation - Rat	658 mg/l/4h
-----------------------	-------------

Skin corrosion/irritation : Causes skin irritation.
pH: 6.31 – 6.41

Mold Release Lubricant

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Serious eye damage/irritation	: Not classified pH: 6.31 – 6.41
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Suspected of damaging fertility.
STOT-single exposure	: May cause drowsiness or dizziness.

Hexane

STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Causes damage to organs (nervous system) through prolonged or repeated exposure (Inhalation).

Hexane

STOT-repeated exposure	STOT RE 1 C \geq 5 %
Aspiration hazard	: May be fatal if swallowed and enters airways.
Symptoms/effects after inhalation	: Aspiration of the product into the lungs may cause very serious pneumonia. May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Irritation (itching, redness, blistering).
Symptoms/effects after eye contact	: May cause eye irritation.
Symptoms/effects after ingestion	: Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis.
Most Important Symptoms/Effects	: Risk of product entering the lungs on vomiting after ingestion.
Chronic symptoms	: Causes damage to organs (nervous system) through prolonged or repeated exposure (inhalation). Suspected of damaging fertility.

SECTION 12 Ecological information

12.1. Ecotoxicity

Hazardous to the aquatic environment, short-term (acute)	: Toxic to aquatic life
Hazardous to the aquatic environment, long-term (chronic)	: Toxic to aquatic life with long lasting effects

Hexane

LC50 - Fish [1]	> 1 mg/l
EC50 - Crustacea [1]	3.9 mg/l

12.2. Persistence and degradability

Mold Release Lubricant

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

Hexane

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

Silicone oil

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

Mold Release Lubricant

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Propane	
Persistence and degradability	Not rapidly degradable

Butane	
Persistence and degradability	Not rapidly degradable

Isobutane	
Persistence and degradability	Not rapidly degradable

12.3. Bioaccumulative potential

Hexane	
Partition coefficient n-octanol/water (Log Pow)	3.9

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone : Not classified
Fluorinated greenhouse gases : No

SECTION 13 Disposal considerations

Regional waste regulation : Disposal must be done according to official regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations : Disposal must be done according to official regulations.
Product/Packaging disposal recommendations : Disposal must be done according to official regulations. Dispose of this material and its container at hazardous or special waste collection point. Refer to all applicable national, international and local regulations or provisions.
Additional information : Do not re-use empty containers.
Ecological waste information : Avoid release to the environment.
List of Hazardous Wastes Codes : U.S. - RCRA (Resource Conservation Recovery Act) - D Waste- Characteristic Waste Codes. D001: IGNITABLE WASTE.

SECTION 14 Transport information

In accordance with DOT / IMDG / IATA

DOT	IMDG	IATA
14.1. UN number		
UN1950	1950	1950
14.2. Proper Shipping Name		
Aerosols	AEROSOLS	Aerosols, flammable
14.3. Transport hazard class(es)		
2.1	2.1	2.1
14.4. Packing group		
Not applicable	Not applicable	Not applicable

Mold Release Lubricant

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

DOT	IMDG	IATA
14.5. Environmental hazards		
	Dangerous for the environment: No Marine pollutant: Yes	
No supplementary information available		

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

DOT	
UN-No. (DOT)	: UN1950
DOT Packaging Exceptions (49 CFR 173.xxx)	: 306
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 75 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 150 kg
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other	: 25 - Shade from radiant heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

IMDG	
Special provision (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG)	: SP277
Excepted quantities (IMDG)	: E0
Packing instructions (IMDG)	: P207, LP200
Packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
EmS-No. (Spillage)	: S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

IATA	
PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
ERG code (IATA)	: 10L

SECTION 15 Regulatory information

15.1. Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Mold Release Lubricant

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Hexane	CAS-No. 110-54-3	32%
--------	------------------	-----

Hexane (110-54-3)

Listed on EPA Hazardous Air Pollutant (HAPS)
Listed on EPA HAPs Acute Dose Response Assessment List – Exposure limits

CERCLA RQ	5000 lb
-----------	---------

15.2. International regulations

CANADA

Hexane (110-54-3)

Listed on the Canadian DSL (Domestic Substances List)

Silicone oil (63148-62-9)

Listed on the Canadian DSL (Domestic Substances List)

Propane (74-98-6)

Listed on the Canadian DSL (Domestic Substances List)

Butane (106-97-8)

Listed on the Canadian DSL (Domestic Substances List)

Isobutane (75-28-5)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

Hexane (110-54-3)

Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on EPA HAPs Acute Dose Response Assessment List – Exposure limits

Silicone oil (63148-62-9)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Propane (74-98-6)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Butane (106-97-8)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Mold Release Lubricant


Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Isobutane (75-28-5)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. State regulations

 **WARNING:** This product can expose you to n-Hexane, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Component	State or local regulations
Hexane(110-54-3)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List
Propane(74-98-6)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List
Butane(106-97-8)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List
Isobutane(75-28-5)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16 Other information

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Issue date : 9/12/2025

Full text of hazard classes and H-statements	
H220	Extremely flammable gas
H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapor
H229	Pressurized container; may burst if heated
H280	Contains gas under pressure; may explode if heated
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H372	Causes damage to organs through prolonged or repeated exposure
H401	Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects
SIAS	May displace oxygen and cause rapid suffocation

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.